



# BG-Solv™ 717

## Ink and Graffiti Cleaner

### Product Description

BG-Solv™ 717 is a powerful solvent cleaner designed for high penetration and rapid removal of ink and graffiti from hard surfaces. The product also is effective at removing grease, oil residue, and dirt. It works well on metals, painted surfaces, and some plastics. Application areas include schools, offices, subways, bus stations, factories, or any place that unwanted dirt and graffiti have appeared.

**BG-Solv™ 717 aggressively penetrates and removes inks and graffiti from most non-porous surfaces restoring them to original condition.**

BG-Clean™ 717 offers significant advantages compared to other cleaners including:

- ☑ BG-Clean™ 717 cleans as well as chemicals such as Methylene Chloride, but without the negative safety and environmental impacts.
- ☑ BG-Clean™ 717 not only works on inks and paints but also can clean oil and grease, making it a dual use product.
- ☑ BG-Clean™ 717 rinses clean with water and leaves no residue behind.
- ☑ BG-Clean™ 717 is safe to store, handle, and use and is 100% rapidly biodegradable.
- ☑ BG-Clean™ 717 is cost effective providing for a long term economical solution.
- ☑ BG-Clean™ 717 can be applied by hand or in conjunction with power washers.



### Product Application

Remove any heavy buildup from the surface to be cleaned by scraping or wiping the area. If water is used during surface preparation, the area should be allowed to dry before proceeding. Spray, wipe, or mop BG-Solv™ 717 over the surface to be cleaned and allow it to penetrate for 5 to 10 minutes.

Next agitate the surface with a brush or high pressure water. Last, rinse the surface with clean water and repeat the process as necessary. Hot water and high pressure will speed the cleaning process in most cases. Use absorbent materials or a wet vacuum to contain any water or chemical which runs off during the cleaning process.

### Technical Data

Chemical Type: Solvent Based Surfactant Mixture  
Solubility in Water: 90% miscible  
Oil Emulsifying Capability: Medium/High  
Oil Dispersant Capability: Low  
Dilution Rate: Ink/Graffiti: 20-100%; Oil: 10-20%  
Penetration: High

Flash Point: >160F  
Boiling Point: >330F  
Odor: Mild Fresh Scent  
pH: Not Applicable  
Biodegradability: 100%; 90% within 21 days  
HMIS (Safety): 1-1-0-C